

AUGUST 28, 2020

# PRODUCT ANNOUNCEMENT

## BP99-65003

### Trailer Bumper

Utility: RDB003

**Application:**  
Utility Trailer

**Dimensions:**  
Length: 5-3/4"  
Width: 3"  
Height: 3"  
Bolt Size: 1/2"  
Bolt Holes: 3-1/2" c-c



**Quantity Per Vehicle:** 2

## Did You KNOW?

- Today's typical rubber bumpers do not last very long and may be worn out in six to twelve months.
- ATRO's polyurethane bumpers have been proven to last as much as 15 times longer than rubber.

### ! Things TO CONSIDER

- Labor Cost
- Downtime
- Trailer Damage

Changing out a simple trailer bumper can present a technician with unexpected problems. Many of today's bumpers are mounted into a sealed bumper frame that contains the stop/tail/turn lamps. Often, a lamp will need to be removed to gain access to the rusted nuts on the inside of the trailer bumper frame. This is further complicated when the lamp is secured with a riveted lock ring, common with the newer LED powered stop/tail/turn lamps. The bumper removal process usually takes a minimum of 20 minutes and as much as 45 minutes to complete and often the lamp gets damaged in the process.

Changing out a simple trailer bumper can present a technician with unexpected problems. Many of today's bumpers are mounted into a sealed bumper frame that contains the stop/tail/turn lamps. Often, a



PA011-082820

**ATRO**  
ENGINEERED SYSTEMS

**WITH ATRO BEHIND YOU,  
DRIVE FORWARD.**

SUSPENSION » TORQUE ROD » TRAILER » UNDERHOOD

6 Bolte Lane  
St. Clair, Missouri 63077 | U.S.A.  
(800) 325.6114 | Fax (866) 920.2005  
[www.atrobushing.com](http://www.atrobushing.com)

©2020 ATRO ENGINEERED SYSTEMS, INC.

ATRO Engineered Systems, Inc. is not liable for any errors herein. All manufacturers' names and part numbers are used without permission; no endorsement, affiliation, or recommendation is implied. They are included for reference purposes only.